

SMART BATTERY CHARGER – 12V/50A & 24V/25A



Features

- Microprocessor Controller Inside
- Full Range Input
- Power Factor Correction >0.97
- High Efficiency >90% (230VAC)
- 4 Stages Charging : I–Uo–U
-Equalization
- Battery Charger and Power Supply
Selectable
- Compact and Light Weight

WSC-1250, WSC-2425




RC-600



RC-601D



TF-100



Specifications

| Model No. | WSC-1250 | WSC-2425 |
|-------------------------------|--|--|
| Input voltage range | 100-240VAC | |
| Input frequency | 50-60Hz | |
| Power factor correction | >0.97 | |
| Efficiency at 230VAC | >91% | >93% |
| Efficiency at 115VAC | >89% | >91% |
| Input current at 230VAC | 3.62A | 3.51A |
| Input current at 115VAC | 7.32A | 7.1A |
| Charge mode | Normal 3-stage/Equalization 4 - stage | Normal 3-stage/Equalization 4 - stage |
| Output charging voltage | 14V/14.4V/14.8V | 28V/28.8V/29.6V |
| Output float voltage | 13.5V/13.8V | 27V/27.6V |
| Output power mode voltage | 13.2V | 26.4V |
| Output charging current | 0-50A | 0-25A |
| Equalization mode | 14.8V/15.5V (0-25A) | 29.6V/31V (0-12.5A) |
| Half power mode (silent mode) | 0-25A | 0-12.5A |
| Battery connection | 3 | 3 |
| Battery types | Lead-acid/GEL/AGM/Li-Ion | Lead-acid/GEL/AGM/Li-Ion |
| Battery capacity | 500Ah | 250Ah |
| Operating temperature | -20 ° C ~ +50 ° C | -20 ° C ~ +50 ° C |
| Storage temperature | -40 ° C ~ +85 ° C | -40 ° C ~ +85 ° C |
| Air humidity | 10 - 90% | 10 - 90% |
| Option: Remote Control | RC-600 or RC-601D | RC-600 or RC-601D |
| Option: Temperature sensor | TF-100 | TF-100 |
| Dimensions (mm)LxWxH | 292*210*75 | 292*210*75 |
| Weight | 2.5 kgs | 2.5 kgs |
| Protective devices | Short circuit protection Over voltage protection Over current protection Battery charger over temperature Battery over temperature | Short circuit protection Over voltage protection Over current protection Battery charger over temperature Battery over temperature |